AED Maintenance Check
Daily, Monthly, Yearly
School Year

AED ID#: _	
(ID # can be	found on back of AED)
Location of	f Unit:

School:

-									Check the STATUS INDICATOR to ensure that it is GREEN. When the indicator is GREEN, the Powerheart AED G3 is ready for a rescue. If the indicator is RED, refer to the Troubleshooting																						
Daily	Daily Maintenance CheckTable in the manual, located in the AED carrying case.																														
Date	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Aug																															
Sept																															
Oct																															
Nov																															
Dec																															
Jan																															
Feb																															
Mar																															
Apr																															
May																															
Jun																															
Jul																															

(Please initial each box)

Monthly Maintenance Check (please initial)

Aug	 Feb	
Sept	 Mar	
Oct	 Apr	
Nov	 May	
Dec	 Jun	
Jan	 Jul	

Monthly Maintenance:

- 1. Open the AED lid.
- 2. Wait for the AED to indicate status.
- 3. Observe the change of the STATUS INDICATOR to RED. After less than 5 seconds, verify that the STATUS INDICATOR returns to GREEN.
- 4. Listen to the voice prompts.
- 5. Close the lid and confirm that STATUS INDICATOR remains GREEN, (for the Powerheart AED G3 only).

Yearly Maintenance Check: Date _____

(please initial)

- Yearly Maintenance:
 - 1. Open the AED lid.
 - 2. Remove the electrodes.
 - 3. Close the lid.
 - 4. Confirm that the STATUS INDICATOR turns RED.
 - 5. Open the lid and confirm that the Electrode Indicator is lit.
 - 6. Reconnect the electrodes and close the lid.

- 7. Make sure the expiration date is visible through the clear window of the lid. a. check to make sure that the STATUS INDICATOR is GREEN.
- 8. Open the lid and confirm that no diagnostic indicators are lit.
- 9. Check the expiration date of the electrodes.
- 10. Check the electrode's packaging integrity.
- 11. Close the lid.